



Specifications:

Housing: LCP UL94-V0 Color: Nature  
 Contact: Phosphor Bronze Gold Plated  
 Operating Voltage: 50V AC/DC  
 Current Rating: 1A AC/DC  
 Withstand Voltage: 250V AC/Minute  
 Contact Resistance:  $\leq 20\text{m}\Omega$   
 Insulation resistance:  $\geq 100\text{m}\Omega$   
 Operating Temperature:  $-25^{\circ}\text{C} \sim +85^{\circ}\text{C}$

CKTS	DIM A	DIM B	DIM C
010	4.0	7.3	5.4
012	5.0	8.3	6.4
016	7.0	10.3	8.4
018	8.0	11.3	9.4
020	9.0	12.3	10.4
024	11.0	14.3	12.4
030	14.0	17.3	15.4
034	16.0	19.3	17.4
040	19.0	22.3	20.4
050	24.0	27.3	25.4
060	29.0	32.3	30.4

一般公差  
 TOLERANCES  
 X.  $\pm 0.40$  .XX  $\pm 0.20$   
 .X  $\pm 0.30$  .XXX  $\pm 0.10$   
 ANGLES  $\pm 2^{\circ}$

深圳市宏利电子有限公司  
 Shenzhen Holy Electronic Co.,Ltd

检验尺寸标示  
 SYMBOLS  $\odot$   $\ominus$  INDICATE  
 CLASSIFICATION DIMENSION  
 $\odot$  MARK IS CRITICAL DIM.  
 $\ominus$  MARK IS MAJOR DIM.

工程  
 图号 WTB1042LW-2\*nP 制图 (DR)  
 '08/5/16  
 品名 WTB1.0mm LW - 2\*nP 审核 (CHKD)  
 立式母座  
 TITLE 1.0mm Wire To Board  
 Connector 核准 (APPD)  
 Rigo Lu

修订 REV	修改摘要 REVISION DESCRIPTION	日期 DATE	签名 SIGNATURE
-	-	-	-

表面处理 (FINISH)  
 比例 (SCALE) 1:1  
 单位 (UNITS) mm

张数 (SHEET) 1 OF 1  
 尺寸 (SIZE) A4  
 版本 (REV) 0